Safety Data Sheet

Copyright,2015,3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	18-0723-9	**Version Number:**	8.00
Issue Date:	04/16/15	**Supercedes Date:**	04/13/15

SECTION 1: Identification

1.1. Product identifier
3M(TM) Scotch-Weld(TM) Urethane Adhesive DP604NS Black and Urethane Adhesive 604NS Black, Part A

Product Identification Numbers
62-2748-8530-0, 62-2748-9530-9

1.2. Recommended use and restrictions on use

Recommended use
Structural adhesive

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification
Serious Eye Damage/Irritation: Category 2A.
Skin Corrosion/Irritation: Category 2.
Respiratory Sensitizer: Category 1.
Skin Sensitizer: Category 1.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements
Signal word
Danger

Symbols
Health Hazard |

Pictograms

Hazard Statements
Causes serious eye irritation.
Causes skin irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary Statements

Prevention:
Do not breathe dust/fume/gas/mist/vapors/spray.
In case of inadequate ventilation wear respiratory protection.
Wear protective gloves and eye/face protection.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:
IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Get medical advice/attention if you feel unwell.

Disposal:
Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified
Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

36% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
polyurethane prepolymer	67837-35-8	40 - 70 Trade Secret *
dicyclohexylmethane-4,4'-diisocyanate (HMDI)	5124-30-1	15 - 40 Trade Secret *
4,4'-diphenylmethane diisocyanate	101-68-8	1 - 5 Trade Secret *
1,1'-diphenylmethane diisocyanate polymer	39310-05-9	1 - 5 Trade Secret *
carbon black	1333-86-4	0.05 - 0.5 Trade Secret *
1,1'-methylenebis(isocyanatobenzene)	26447-40-5	<= 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes	During Combustion
Isocyanates	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Cyanide	During Combustion
Oxides of Nitrogen	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters
No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation

to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial or professional use only. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities
Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
4,4'-diphenylmethane diisocyanate	101-68-8	ACGIH	TWA:0.005 ppm	
4,4'-diphenylmethane diisocyanate	101-68-8	OSHA	CEIL:0.2 mg/m3(0.02 ppm)	
FREE ISOCYANATES	101-68-8	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	
carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
carbon black	1333-86-4	CMRG	TWA:0.5 mg/m3	
carbon black	1333-86-4	OSHA	TWA:3.5 mg/m3	
FREE ISOCYANATES	26447-40-5	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	
dicyclohexylmethane-4,4'-diisocyanate (HMDI)	5124-30-1	ACGIH	TWA:0.005 ppm	
FREE ISOCYANATES	5124-30-1	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.
Gloves made from the following material(s) are recommended: Butyl Rubber
Fluoroelastomer
Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Viscous liquid
Odor, Color, Grade:	Low or no detectable odor, black.
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*No Data Available*
Boiling Point	>=400 ºF
Flash Point	>=290 ºF [*Test Method:* Tagliabue Closed Cup]
Evaporation rate	<=1 [*Details:* Gels with exposure to humidity.]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	<=0.000004 mmHg [@ 68 ºF]

Vapor Density	>=1 [*Ref Std:* AIR=1]
Density	1.056 g/ml [*Ref Std:* WATER=1]
Specific Gravity	1.056
Solubility in Water	Negligible
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Viscosity	1,500 - 2,400 centipoise [@ 20 ºC] [*Test Method:* Brookfield]
Hazardous Air Pollutants	<= 5 % weight [*Test Method:* Calculated]
VOC Less H2O & Exempt Solvents	0.5 g/l [*Test Method:* calculated SCAQMD rule 443.1] [*Details:* when used as intended with Part B]
VOC Less H2O & Exempt Solvents	1 g/l [*Test Method:* calculated SCAQMD rule 443.1] [*Details:* as supplied]
VOC Less H2O & Exempt Solvents	0.05 % [*Test Method:* calculated SCAQMD rule 443.1] [*Details:* when used as intended with Part B]

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials
Water
Strong acids
Strong bases
Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

Skin Contact:
Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:
Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:
Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE > 50 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
dicyclohexylmethane-4,4'-diisocyanate (HMDI)	Dermal	Rabbit	LD50 > 10,000 mg/kg
dicyclohexylmethane-4,4'-diisocyanate (HMDI)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.434 mg/l
dicyclohexylmethane-4,4'-diisocyanate (HMDI)	Ingestion	Rat	LD50 9,900 mg/kg
4,4'-diphenylmethane diisocyanate	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
4,4'-diphenylmethane diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-diphenylmethane diisocyanate	Inhalation-Dust/Mist	Rat	LC50 0.369 mg/l

	(4 hours)		
4,4'-diphenylmethane diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
1,1'-methylenebis(isocyanatobenzene)	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
1,1'-methylenebis(isocyanatobenzene)	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,1'-methylenebis(isocyanatobenzene)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.369 mg/l
1,1'-methylenebis(isocyanatobenzene)	Ingestion	Rat	LD50 31,600 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4,4'-diphenylmethane diisocyanate	official classification	Irritant
carbon black	Rabbit	No significant irritation
1,1'-methylenebis(isocyanatobenzene)	official classification	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
4,4'-diphenylmethane diisocyanate	official classification	Severe irritant
carbon black	Rabbit	No significant irritation
1,1'-methylenebis(isocyanatobenzene)	official classification	Severe irritant

Skin Sensitization

Name	Species	Value
4,4'-diphenylmethane diisocyanate	official classification	Sensitizing
1,1'-methylenebis(isocyanatobenzene)	official classification	Sensitizing

Respiratory Sensitization

Name	Species	Value
4,4'-diphenylmethane diisocyanate	Human	Sensitizing
1,1'-methylenebis(isocyanatobenzene)	Human	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
4,4'-diphenylmethane diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
carbon black	In Vitro	Not mutagenic
carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification
1,1'-methylenebis(isocyanatobenzene)	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
4,4'-diphenylmethane diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not

			sufficient for classification
carbon black	Dermal	Mouse	Not carcinogenic
carbon black	Ingestion	Mouse	Not carcinogenic
carbon black	Inhalation	Rat	Carcinogenic
1,1'-methylenebis(isocyanatobenzene)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
4,4'-diphenylmethane diisocyanate	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 0.004 mg/l	during organogenesis
1,1'-methylenebis(isocyanatobenzene)	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 0.004 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,4'-diphenylmethane diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
1,1'-methylenebis(isocyanatobenzene)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,4'-diphenylmethane diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
carbon black	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,1'-methylenebis(isocyanatobenzene)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit **http://3M.com/Transportinfo** or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations
Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
4,4'-diphenylmethane diisocyanate	101-68-8	1 - 5
4,4'-diphenylmethane diisocyanate (DIISOCYANATES (CERTAIN CHEMICALS ONLY))	101-68-8	1 - 5
4,4'-diphenylmethane diisocyanate (Benzene, 1,1'-methylenebis[4-isocyanato-)	101-68-8	1 - 5
dicyclohexylmethane-4,4'-diisocyanate (HMDI) (DIISOCYANATES (CERTAIN CHEMICALS ONLY))	5124-30-1	15 - 40
dicyclohexylmethane-4,4'-diisocyanate (HMDI)	5124-30-1	15 - 40

15.2. State Regulations
Contact 3M for more information.

15.3. Chemical Inventories
The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification
Health: *2 **Flammability:** 1 **Physical Hazard:** 1 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	18-0723-9	**Version Number:**	8.00
Issue Date:	04/16/15	**Supercedes Date:**	04/13/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com