



ARMOR GUYS

• PROTECTED •

EXTRAFLEX

04-200 SPECIFICATION SHEET



EN388



4232B



SPECIFICATIONS

LINER MATERIALS	Yellow Engineered Yarn
COATING MATERIALS	Black HCT MicroFoam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	XS -XXL

PACKAGING						
CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	120	120	120	120	120	120
CASE WEIGHT	13.22/lbs	13.66/lbs	14.10/lbs	15.42/lbs	16.08/lbs	17.18/lbs
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Light Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4331						
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

FEATURES

LINER

18g, Yellow Engineered Yarn

COATING

Black HCT MicroFoam Nitrile Palm Coating

BENEFITS:

ANSI Cut Level A2
EN 388 Cut Level 3
"All in one" : Fit, Feel, Flexibility, Breathability, Durability
Excellent Wet Grip

CATEGORY:

Extraflex

APPLICATIONS:

Appliance Manufacturing
Automotive Assembly
Electronic Component Assembly
Handling Small, Sharp, Oily Parts
HVAC/Sheet Metal
Metal Fabrication
Micro Engineering
Pulling Electrical Wires

Armor Guys reference number : 04-200

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:

