Revision Number: 003.0 **Issue date:** 11/06/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: **AQUENCE PL 0857 KNOWN AS DORUS PL 0857**
Product type: Adhesive
Restriction of Use: None identified
Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

IDH number: 1218308
Region: United States
Contact information:
Telephone: (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW
NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)
None

Precautionary Statements

Prevention: Not prescribed
Response: Not prescribed
Storage: Not prescribed
Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Vinyl acetate	108-05-4	1 - 5

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Wash with soap and water. If symptoms develop and persist, get medical attention.

Eye contact: If irritation develops, flush eyes immediately with large amounts of water. If irritation persists, seek medical attention or advice.

Ingestion: Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. If symptoms develop and persist, get medical attention. Never give anything by mouth to an unconscious person.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Use extinguishing measures appropriate to local circumstances and the surrounding environment. Water spray or fog. foam Carbon dioxide. Dry chemical.

Special firefighting procedures: Fire fighters should wear full-face, self contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

Unusual fire or explosion hazards: This product is an aqueous mixture which will not burn. If evaporated to dryness, the solid residue may pose a moderate fire hazard. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: No special environmental precautions required. Do not allow material to contaminate ground water system.

Clean-up methods: Take up with liquid-absorbing material (sand). Wash spillage site thoroughly with soap and water or detergent solution. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling: Avoid extreme temperatures. Protect from freezing. This material should not be spilled, discharged, or flushed into sewers or public waterways. Product contains low level of organic volatiles which could accumulate in the unvented headspace of drums or bulk storage vessels. Open drums in well ventilated area. Avoid breathing vapors.
Do not wear contact lenses.

Storage: For safe storage, store between 1 °C (33.8 °F) and 37 °C (98.6 °F)
Below temperature limit the product will be irreversibly damaged and no longer usable. Above temperature limit the product properties change.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Vinyl acetate	10 ppm TWA 15 ppm STEL	None	None	None

Engineering controls:	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. Handle in accordance with good industrial hygiene and safety practice
Respiratory protection:	Under normal conditions, respirator is not normally required. If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.
Eye/face protection:	Wear safety glasses with side shields. Do not wear contact lenses.
Skin protection:	Use of protective coveralls and long sleeves is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	White
Odor:	Acrylic
Odor threshold:	Not available.
pH:	4.0 - 5.0
Vapor pressure:	17.5000000 mm hg (20.0 °C (68°F))
Boiling point/range:	> 100.0 °C (> 212°F)
Melting point/ range:	0.0 °C (32°F) (Freezing point)
Specific gravity:	1.0600
Vapor density:	> 1.0000 (Air = 1)
Flash point:	> 100.00 °C (> 212°F) Closed cup
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Evaporation rate:	1.00 Same as water.
Solubility in water:	Miscible
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 0.60 % (by weight)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials:	This product may react with strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Freezing. Product may be unstable if frozen.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Eyes, Inhalation

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Skin contact: Prolonged and/or repeated skin contact may result in mild irritation or redness.
Eye contact: May cause slight irritation to eyes on contact.
Ingestion: May cause gastrointestinal tract irritation if swallowed. Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Vinyl acetate	Oral LD50 (RAT) = 2,920 mg/kg Dermal LD50 (RABBIT) = 2,335 mg/kg Inhalation LC50 (RABBIT, 4 h) = 2500 ppm Inhalation LC50 (RABBIT, 4 h) = 2511 ppm Inhalation LC50 (RABBIT, 4 h) = 8800 ppm Inhalation LC50 (RAT, 4 h) = 3680 ppm	Central nervous system, Irritant, Mutagen, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Vinyl acetate	No	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: No data available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. This product is not a RCRA hazardous waste when discarded. Processing, use, or contamination of this product may change the hazard classification and waste management options.

Hazardous waste number: None identified.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)
Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)
Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)
Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Vinyl acetate (CAS# 108-05-4).
California Proposition 65:	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status:	One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Jennifer Altman, Sr. Regulatory Affairs Specialist

Issue date: 11/06/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.