

Pro 2.5 MP Fire Extinguisher

Part number 466227

Multipurpose use

Rechargeable

UL Rated 1-A, 10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PRO 2.5MP is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder & sturdy aluminum valve assembly.

Available with metal retention bracket.
Order pt # 46622701

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 2.6 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with optional mounting bracket
- Powder coated cylinder for corrosion protection

At a Glance

- Model PRO 2.5MP
- Multipurpose Dry Chemical
- Rechargeable
- UL listed
- UL rated 1-A, 10-B:C
- U.S.C.G, DOT approved
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:




Pt # 466227 - 6 pack
UPC: 0-47871-66227-2
I2F - 10047871662279
Pt # 46622720 - 6 pack
UPC: 0-47871-22720-4
I2F - 10047871227201
Pt # 46622701 - 6 pack Mtl Brk
UPC: 0-47871-22701-3
I2F - 10047871227010

Product Specification

Net agent weight (Average)	2.6 lb.
Unit weight (Average)	3.9 lb.
Diameter	3.25 inches
Height	14.26 inches
Discharge time	8-12 seconds
Discharge range	10-15 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Packaging dimensions (inches)

	Depth	Width	Height
Carton	3.62	5.5	15.81
Master Pack	11.93	16.25	11.0



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com